

NOTE: CERTIFICATION OF MATERIAL COMPLIANCE REQUIRED. COMPLETED ASSEMBLY MUST BE (RoHS) COMPLIANT PER VICOR SPEC CST-0001.

REVISIONS ECO REV DESCRIPTION APPROVED DATE 367 A PRODUCTION RELEASE 2/3/95 RBD 421 B NOTE 2.1 WAS: 1.1MH, IS: 1.3MH 7/18/95 RBD 549 C CHG: NOTE 2.1, WAS: 1.3mH, IS: 0.9-2 AT 1KHz 6/5/96 RBD C1 CHG NOTE 2.1 TO: 0.8 - 1.3 MH AT 1KHZ 03/08/04 RBD 1462 D ADDED ROHS SPEC NOTE 06/21/05 LGK D1 CHG NOTE 2.1 FROM: 1.3 TO: 1.4mH 07/22/05 DAF 1578 E CHG HEIGHT DIM FR: .25 TO .275 (MAX) 06/08/06 DAF E1 CHG NOTE 2 TO MIN O.SmH 07/26/06 DAF 1710 F ADD TEST VOLTAGE TO NOTE 2.1 10/02/06 DAF F1 CHG NOTE 2.1 FR: 1 VOLT TO: SOOMV 01/18/07 DAF F2 ADD CORE TO 1.1 & 2.1 CHG 500 TO 100MV 01/18/07 DAF

NOTES: UNLESS OTHERWISE SPECIFIED.

SH 1 FEY-2

1. MATERIALS: UL RECOGNIZED 94V-2 FLAMMABILITY RATING CLASS B (130°C) REQUIRED.

1.1 CORE: TOROID - .375 X .187 X .188 (u = 5000)

MAGNETICS: ZJ-41005-TC FAIR-RITE: 5975002501 (COATED)

STEWARD: 35T0375-30P

ACME: T9.53 X 4.75 X 4.80 AO5

1.2 WIRE: U.L. RECOGNIZED 130°C RATING MAGNET WIRE.
APPROVED MFR: ESSEX; OTHER MFR HAS TO BE
ROHS COMPLIANT CERTIFIED BEFORE USE

2. SPECIFICATIONS:

2.1 L = MIN 0.8-mH @ 100 mV 1 KHz TEST FREQUENCY

2.2 DCR = 35 mOHMS MAX

3. CONSTRUCTION:

3.1 WIND

3.2 TIN LEADS CLOSE TO CORE AS SHOWN

3.3 LABEL BULK PACKAGE WITH DRAWING NUMBER AND REVISION, VENDOR IDENTIFICATION, AND DATE OF MANUFACTURE.

		UNLESS OTHERSISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ±1/32 .XX ±.01 ±1/2*	CONTRACT NO.		WESTCOR & division of MCCOR Corp.					
		.XXX ±.005	APPROVALS	DATE		11101107	05 4			
		SEE NOTE 1		10/13/84		INDUCT	OR 1	MH	I TOROID	İ
	SEE MIS	FINSH	CHECKED HONDO	01/26/95	SIZE	CAGE CODE	DWC NO.			1
NEXT ASSY	USED ON	NONE		10/13/84	1 -					F2
APPLICATION		DO NOT SCALE DRAWING	DESIGNED R. DRABING	10/13/94	SCALE	NTS PLENAME	36-00030	.DWG 9	HEET 1 OF	1