




VICOR CONFIDENTIAL

THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF VICOR CORP.

REV.	DESCRIPTION	INTL	DATE	APVD
1	REVISED PER E071233	REJH	06/15/07	EM
2	REVISED PER E090673c	AR	04/22/09	REJH
3	REVISED PER E064291	JS	09/10/09	REJH
4	REVISED PER E101310b	KUK	10/22/10	AR
5	REVISED PER E170323a	YG	04/03/17	REJH
6	REVISED PER E180886	AY	01/10/19	RLT
7	REVISED PER E230152	ALT	3/2/23	SD




DETAIL :
 A. SPLIT RELEASE LINER.
 B. ADHESIVE STRIP; .0025 THICK .188 WIDE.
 C. ALUMINUM ALLOY 1145-0; .002 THICK.
 D. PHASE CHANGE THERMAL COMPOUND; .001 THICK.
 E. PHASE CHANGE THERMAL COMPOUND; .0005 THICK.



SECTION A-A

- NOTES:**
1. MATERIAL: MAKE FROM TIMTEL ACTAPHASE 60 (AL2X-L10-S-452-232). (VERTICAL THICKNESS IS NOT SHOWN TO SCALE)
 2. THICKNESS: .007±.001.
 3. SEE DETAIL FOR ASSY ORDER.
 4. FOR ARTWORK SHOWN HERE SEE DWG# 20200.
 5. ○ DENOTE CRITICAL CHARACTERISTIC FOR LOT INSPECTION.
 6. RoHS COMPLIANT PER CST-0001 LATEST REVISION.
 7. PRIOR TO ASSEMBLY, PRODUCTS SHALL BE STORED IN A COOL, DRY LOCATION IN ORIGINAL PACKAGING AT TEMPERATURES BELOW 40±C (104±F). UNDER THESE CONDITIONS THE SHELF LIFE IS INDEFINITE. THERMMATE PADS CAN BE PRE-APPLIED TO BASEPLATES OR HEAT SINKS WHICH ARE THEN SHIPPED TO A FINAL ASSEMBLY LOCATION, AS LONG AS THE TEMPERATURE DOES NOT EXCEED THE LEVEL INDICATED ABOVE.

DRAWN BY Krishna Kamath	DATE 5/14/2010	VICOR SWD			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE : INCH / [MM]		THERMAL INTFC PAD, TMATEVI-200			
TOLERANCES ARE: DECIMALS ANGLES X.XX [X.X] = ±0.01 [0.25] ±1° X.XXX [X.XX] = ±0.005 [0.127]		SIZE B	CAGE CODE 67131	DWG NO 19459	REV 7
THIRD ANGLE PROJECTION  DO NOT SCALE DRAWING		SCALE 1:1	SHEET 1 OF 1		